

6

5

4

3

2

1

APPROVED: _____

DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	11/23/10	
A		UPDATE SPEC.	6/27/16	AY/SC

D

D

C




C

B

B

A

A



Positions: 2 thru 15

A = .079 [2.00] x No. of Spaces

B = .079 [2.00] x No. of Spaces + .157 [4.00]

SPECIFICATIONS:

Material:
Insulator: NY66, rated UL 94V-0
Insulator color: Natural

Electrical:
Voltage rating: 250 VAC/DC
Current rating: 3A AC/DC max, 22AWG
Insulation resistance: 1,000 Mohms min
Dielectric withstanding voltage: 800 VAC for 1 minute

Temperature Rating:
Operating temperature: -25°C to +85°C

Environmental:
Lead free, RoHS compliant



UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	∅X	± .10
.XX	± .020	∅XX	± .015
.XXX	± .015	∅XXX	± .010

ADAM TECH

909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

APPROVALS		DATE
DRAWN	AY	11/23/10
CHECKED	AH	11/23/10
APPROVED		

TITLE .079 [2.00] CRIMP HOUSING			
SIZE X	PART NO. 2CH-H-XX	REV. A	
REF: S00015T	SCALE: NTS	SHEET 1 OF 1	

6

5

4

3

2

1