

6 5 4 3 2 1

APPROVED: _____
DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	3/24/20	

Top view of the battery clip. Dimensions include a total width of 20.30, a distance of 9.85 from the left edge to the centerline, a distance of 2-3.00 between the two contact points, a distance of 2-5.100 from the centerline to the right edge, and a distance of 7.00 between the two contact points.

Side view of the battery clip. Dimensions include a height of 3.90, a distance of 9.40 from the bottom edge to the top edge, and a distance of 2.65 from the left edge to the start of the clip.

Recommended PCB layout showing dimensions: 2-6.10, 2-5.50, 31.40, and 9.85.

RECOMMENDED PCB LAYOUT

Bottom view of the battery clip. Dimensions include a height of 4.30, a distance of 21.40 between the two contact points, a height of 3.50, and a total length of 30.40±0.3.

SPECIFICATIONS:
Material: Phosphor Bronze, Nickel plated. T=0.25mm
Environmental:
Lead free, RoHS compliant

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE MILLIMETERS
TOLERANCES: EXCEPT AS NOTED
MM ANGLE
X ± 0.30 X ± 1°
X.X ± 0.25 X.X ± 0.5°
X.XX ± 0.20
X.XXX ± 0.10

ADAM TECH INTERCONNECTS
909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
Fax: 908-687-5710

APPROVALS		DATE
DRAWN	LH	3/24/20
CHECKED	MY	3/24/20
APPROVED		

TITLE		
BATTERY CLIP, CR 2032		
SIZE	PART NO.	REV.
X	BH-67E-5	-
REF: S00136C	SCALE: NTS	SHEET 1 OF 1

6 5 4 3 2 1