

6 5 4 3 2 1

APPROVED: \_\_\_\_\_  
DATE: \_\_\_\_\_ TITLE: \_\_\_\_\_

Rev	AWO #	Description	Date	Appr
-		RELEASED	3/12/20	

**SPECIFICATIONS:**  
**Material:**  
 Housing: PA66, rated UL94V-0, Color: Black  
 Contact: Phosphor Bronze, Nickel plated  
**Electrical:**  
 Contact resistance: 30 Milliohms max  
 Insulation resistance: 1,000 Megohms ohms min  
 Dielectric Voltage: 500 VAC @ sea level  
 Temperature Rating:  
 Operating temperature: -55°C to +105°C  
**Environmental:**  
 Lead free, RoHS compliant

UNLESS OTHERWISE SPECIFIED  
 ALL DIMENSIONS ARE MILLIMETERS  
 TOLERANCES: EXCEPT AS NOTED  
 MM ANGLE

X	± 0.30	X	± 1°
X.X	± 0.25	X.X	± 0.5°
X.XX	± 0.20		
X.XXX	± 0.10		

APPROVALS		DATE
DRAWN	LH	3/12/20
CHECKED	MY	3/12/20
APPROVED		

**ADAM TECH INTERCONNECTS** 909 Rahway Avenue,  
 Union, NJ 07083  
 Phone: 908-687-5000  
 Fax: 908-687-5710

TITLE		BATTERY HOLDER, PCB THRU HOLE FOR 2032, DIP TYPE	
SIZE	PART NO.	REV.	
X	BH-123A-1	-	
REF:	S00136C	SCALE:	NTS
		SHEET 1 OF 1	

6 5 4 3 2 1