





Rev	AWO #	Description	Date	Appr
-		RELEASED	11/5/03	

APPROVED: _____
 DATE: _____ TITLE: _____



RECOMMENDED PCB LAYOUT



SPECIFICATIONS:

- Material: Insulator: Hi-Temp Nylon 6T, rated UL 94V-0
- Insulator color: Black
- Contacts: Brass
- Plating: Gold Flash over Nickel underplate overall
- Electrical: Current rating: 1 Amp max.
- Contact resistance: 20 mohms max. initial
- Insulation resistance: 5,000 Mohms min.
- Dielectric withstanding voltage: 1,000 VAC for 1 minute
- Temperature Rating: Operating temperature: -40°C to +105°C
- Environmental: Lead free, RoHS compliant

A = .079 [2.00] X No. of Spaces + .362 [9.20]
 B = .079 [2.00] X No. of Spaces

UNLESS OTHERWISE SPECIFIED
 ALL DIMENSIONS ARE MM [INCHES]
 TOLERANCES: EXCEPT AS NOTED

.X	± .10	ØXX	± .10
.XX	± .020	ØXXX	± .015
.XXX	± .015	ØXXX	± .010
APPROVALS	DATE		

DRAWN	SLS	11/5/03
CHECKED		
APPROVED		

ADAM TECH

909 Rahway Avenue, Union, NJ 07083
 Phone: 908-687-5000 Fax: 908-687-0214

TITLE: 2.0MM BOX HEADER, VERTICAL, GOLD FLASH, SURFACE MOUNT

SIZE	PART NO.	REV.
X	2BHR-XX-VUA-SMT	-
REF:	SCALE: NTS	SHEET 1 OF 1

