



APPROVED: \_\_\_\_\_  
 DATE: \_\_\_\_\_ TITLE: \_\_\_\_\_

Rev	AWO #	Description	Date	Apr
-		RELEASED	5/5/14	
A		REVISED SPEC.	6/4/14	HR/VY
B		REVISED LAYOUT DIM.	11/25/14	AY/MY
C		UPDATE DRAWING	3/29/18	AY/KC



**SPECIFICATIONS:**

Material:  
 Insulator: PA66, rated UL 94V-0  
 Insulator color: Green  
 Contact: Brass, Tin plated  
 Electrical:  
 Voltage rating: 300 V  
 Current rating: 8A  
 Contact resistance: 20 mohms max  
 Insulation resistance: 500 Mohms min @ 500 VDC  
 Dielectric withstanding voltage: 2,000 VAC for 1 minute  
 Temperature Rating:  
 -40°C to +105°C  
 Environmental:  
 Lead free, RoHS compliant.



Positions: 02 thru 24

A = .150 [3.81] x No. of Spaces + .181 [4.60]

B = .150 [3.81] x No. of Spaces

UNLESS OTHERWISE SPECIFIED  
 ALL DIMENSIONS ARE INCHES [MM]  
 TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	± .10
.XX	± .020	Ø.XX	± .015
.XXX	± .015	Ø.XXX	± .010

**ADAM TECH INTERCONNECTS**  
 909 Rahway Avenue,  
 Union, NJ 07083  
 Phone: 908-687-5000  
 Fax: 908-687-5710

APPROVALS		DATE
DRAWN	HR	5/5/14
CHECKED	SY	5/5/14
APPROVED		

TITLE			
TERMINAL BLOCK, RIGHT ANGLE, .150" [3.81] PITCH			
SIZE	PART NO.	REV.	
X	EBSA-XX-B	C	
REF:	S00067C	SCALE:	NTS
		SHEET 1 OF 1	