

FEATURES:

- 30 Watt DIL Package
- 4:1 Wide Input Voltages
- Efficiency to 89%
- PI Input Filter
- 100% Burned In
- UL 94V-0 Package Material
- Custom Solutions Available
- Regulated Output Types
- UL Recognized
- RoHS Compliant



30 Watt DC-DC Converter
RQ9P-24D12R

Wide Input Voltage Range
30 Watt DC/DC Converter



Input Specifications

Input Voltage:	24Vdc	
Input Voltage Range:	9-36Vdc	@9Vin Min ; 36Vin Max
Under Voltage Shutdown (lock-out circuit)	8.0Vdc Typ	
Remote On/Off	Open or 3~15Vdc(DC/DC ON) Short or 0~1.2Vdc(DC/DC OFF) -0.5 ~ +1.0 mA 2.0 mA TYP	@Positive logic (Standard) (Refer to -Vin PIN) @Input current of Ctrl pin @Remote off input current


Output Specifications

Output Voltage:	±12Vdc	
Output Voltage Accuracy:	±2%	@±11.76~±12.24Vdc @Vin 9~36Vdc
Output Current:	±1250mA	
Efficiency:	89% TYP	@Vin= 24Vdc
Ripple / Noise:	100mVp-p MAX	@20MHz Band width , with 22 uF*2 MLCC
Short Circuit Protection:	Continuous	@Hiccup,auto-recovery
Line Regulation:	±0.5% MAX	@LL to HL at full Load
Load Regulation:	±5.0% MAX	@25% to 100% Load
Over Voltage Protection	16 .5V TYP	@13.5V MIN; 19.6V MAX
Over Load Protection	170% MAX	@% of lout rated; Hiccup mode

General Specifications

Operating Temperature Range:	-40°C ~ +75°C (with derating)	Output load derate 2% per degree Celsius above 50°C as refer to temperature derating graph.
Storage Temperature:	-55°C ~ +125°C	
Switching Frequency:	3300KHz TYP	
Humidity:	95% MAX	
Isolation Voltage:	1500Vdc	
Isolation Resistance:	1000MΩ MIN	
Cooling:	Natural convection	@20LFM
MTBF:	>=1,200,000 Hours	MIL-HDBK-217F@25°C, Ground Benign
Case Material:	Six-side shielded case	
Weight:	22g TYP	
Conducted Emission	EN55032 Class B	(with external components)
Radiated Emission	EN55032 Class B	(with external components)

Temperature Derating Graph




Part Number

RQ9 P - 24 D 12 R
A B C D E F


A: Series
B: Package (P)
C: Input Voltage
D: Dual Output (D)
E: Output Voltage
F: Regulated (R)

Outline Dimensions




Pin	1	2	3	4	5	6
Function	+Vin	-Vin	+Vout	Com	-Vout	NO PIN

Recommended Test Circuit



24V C1 220uF/100V&C2&C3 4.7uF/50V C4&C5 2200pF/2kV L1 0.94mH TVS 3.0SMCJ58AG
48V C1 220uF/100V&C2&C3 4.7uF/100V C4&C5 3200pF/2kV L1 6.20mH TVS 3.0SMCJ120AG

Packaging Information



Unit: mm
Weight: 22 grams/pcs
TUBE: 19 pcs