

6	5	4	3	2	1																																																											
APPROVED: _____			Rev		AWO #	Description	Date	Appr																																																								
DATE: _____ TITLE: _____			-			RELEASED	8/28/14																																																									
			A			UPDATED DRAWING	8/24/23	JJ/RL																																																								
SPECIFICATIONS: Material: Insulator: PA66, rated UL 94V-0 Insulator Color: Green Screw:M2 Contactors: Copper alloy, Nickel plated Electrical: Voltage rating: 300V max Current rating: 8 Amps max Dielectric withstanding voltage: 1,600 VAC for 1 minute Mechanical: Wire range: 28~16 AWG Torque: 0.2Nm Strip length: 6-7mm Temperature Rating: Operating temperature: -40°C to +105°C Environmental: Lead free, RoHS compliant. RoHS COMPLIANT Positions: 2 thru 24 A = .150 [3.81] x No. of Spaces + .181 [4.60] B = .150 [3.81] x No. of Spaces <table><tr><td colspan="3">UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM]. TOLERANCES: EXCEPT AS NOTED</td></tr><tr><td colspan="3">INCHES</td></tr><tr><td>.X</td><td>± .10</td><td>HOLES</td></tr><tr><td>.XX</td><td>± .020</td><td>Ø.X</td><td>± .10</td></tr><tr><td>.XXX</td><td>± .015</td><td>Ø.XX</td><td>± .015</td></tr><tr><td></td><td></td><td>Ø.XXX</td><td>± .010</td></tr><tr><td>DRAWN</td><td>HR</td><td>8/28/14</td><td colspan="2">TITLE</td></tr><tr><td>CHECKED</td><td>YC</td><td>8/28/14</td><td colspan="2">PLUGGABLE BLOCK, PITCH .150 [3.81]</td></tr><tr><td colspan="3">APPROVED</td><td>SIZE</td><td>PART NO.</td></tr><tr><td colspan="3">THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY AND SHOULD NOT BE USED WITHOUT PRIOR WRITTEN PERMISSION FROM ADAM TECH</td><td>X</td><td>EBKA-XX-B-E</td></tr><tr><td colspan="3"></td><td>REF:</td><td>S00067C</td></tr><tr><td colspan="3"></td><td>SCALE:</td><td>NTS</td></tr><tr><td colspan="3"></td><td>SHEET</td><td>1 OF 1</td></tr></table>									UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM]. TOLERANCES: EXCEPT AS NOTED			INCHES			.X	± .10	HOLES	.XX	± .020	Ø.X	± .10	.XXX	± .015	Ø.XX	± .015			Ø.XXX	± .010	DRAWN	HR	8/28/14	TITLE		CHECKED	YC	8/28/14	PLUGGABLE BLOCK, PITCH .150 [3.81]		APPROVED			SIZE	PART NO.	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY AND SHOULD NOT BE USED WITHOUT PRIOR WRITTEN PERMISSION FROM ADAM TECH			X	EBKA-XX-B-E				REF:	S00067C				SCALE:	NTS				SHEET	1 OF 1
UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM]. TOLERANCES: EXCEPT AS NOTED																																																																
INCHES																																																																
.X	± .10	HOLES																																																														
.XX	± .020	Ø.X	± .10																																																													
.XXX	± .015	Ø.XX	± .015																																																													
		Ø.XXX	± .010																																																													
DRAWN	HR	8/28/14	TITLE																																																													
CHECKED	YC	8/28/14	PLUGGABLE BLOCK, PITCH .150 [3.81]																																																													
APPROVED			SIZE	PART NO.																																																												
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY AND SHOULD NOT BE USED WITHOUT PRIOR WRITTEN PERMISSION FROM ADAM TECH			X	EBKA-XX-B-E																																																												
			REF:	S00067C																																																												
			SCALE:	NTS																																																												
			SHEET	1 OF 1																																																												
6	5	4	3	2	1																																																											