






APPROVED: _____

DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	12/16/25	
A		UPDATE DRAWING	1/12/26	WY/RC
B		UPDATE SPEC.	1/21/26	WY/RC



ESMC12D-XX-20C2

POS.	DIM A	DIM B	DIM C	DIM D	DIM E	DIM F
02	2.54	6.83	5.83	8.23	8.83	10.36
03	5.08	9.37	8.37	10.77	11.37	12.90
04	7.62	11.91	10.91	13.31	13.91	15.44
05	10.16	14.45	13.45	15.85	16.45	17.98
06	12.70	16.99	15.99	18.39	18.99	20.52
12	27.94	32.23	31.23	33.63	34.23	35.76

SPECIFICATIONS:

Material:

Insulator: Hi-temp thermoplastic, rated UL 94V-0

Insulator color: Black

Contact: Copper Alloy

Hold Down: Copper Alloy, Tin plated

Plating:

Gold flash over Nickel underplate on contact area,

Tin over Nickel underplate on solder tails

Electrical:

Voltage rating: 180V

Current rating: 24 Amp max (Single Contact)

Contact resistance: 10 mohms max

Insulation resistance: 10,000 Mohms min

Dielectric withstanding voltage: 1390 VAC for 1 minute

Temperature Rating:

Operating temperature: -55°C to +125°C

Environmental:

Lead free, RoHS compliant.



PACKAGED ON TAPE & REEL

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE MILLIMETERS. TOLERANCES: EXCEPT AS NOTED		
MM	.X ± 0.35 .XX ± 0.20 .XXX ± 0.10	ANGLE ± 2°
DRAWN	WY	12/16/25
CHECKED	RC	12/16/25
APPROVED		
CONFIDENTIAL AND PROPRIETARY © Adam Tech. All rights reserved. This document contains confidential and proprietary information belonging to Adam Tech. It is provided solely for design and reference purposes by authorized parties. Any reproduction, distribution, display, or disclosure to third parties, in whole or in part, without the prior written consent of Adam Tech, is strictly prohibited. Adam Tech retains all rights, including copyright, trademark, trade secret, and all other intellectual property rights worldwide.		

ADAM
TECH

909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
adam-tech.com


TITLE
2.54mm POWER BOARD TO BOARD STACKING
CONNECTOR, FEMALE, STRAIGHT, SMT/DIP TYPE

SIZE X	PART NO. ESMC12D-XX-20C2	REV. B
REF: S00242T	SCALE: NTS	SHEET 1 OF 3


APPROVED: _____

DATE: _____ TITLE: _____


Rev	AWO #	Description	Date	Appr
SEE SHT 1 OF 3 FOR REVISION				



Nozzle Cap Dimension



Mating Application— Board to Board Stacking



Mating Application— Daughter Card to Motherboard

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS
ARE MILLIMETERS. TOLERANCES: EXCEPT AS NOTED

MM	.X	± 0.35	ANGLE	± 2°
	.XX	± 0.20		
	.XXX	± 0.10		

DRAWN WY 12/16/25

CHECKED RC 12/16/25

APPROVED

CONFIDENTIAL AND PROPRIETARY
© Adam Tech. All rights reserved. This document contains confidential and proprietary information belonging to Adam Tech. It is provided solely for design and reference purposes by authorized parties. Any reproduction, distribution, display, or disclosure to third parties, in whole or in part, without the prior written consent of Adam Tech, is strictly prohibited. Adam Tech retains all rights, including copyright, trademark, trade secret, and all other intellectual property rights worldwide.

**ADAM
TECH**

909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
adam-tech.com

TITLE 2.54mm POWER BOARD TO BOARD STACKING
CONNECTOR, FEMALE, STRAIGHT, SMT/DIP TYPE


SIZE X PART NO. ESMC12D-XX-20C2 REV. B

REF: S00242T SCALE: NTS SHEET 2 OF 3

APPROVED: _____

DATE: _____ TITLE: _____


Rev	AWO #	Description	Date	Appr
SEE SHT 1 OF 3 FOR REVISION				



SEC. B-B

PULL OUT DIRECTION →

CARRIER DIMENSION - 2P to 3P





SEC. A-A

DETAIL

SEC. B-B

PULL OUT DIRECTION →

CARRIER DIMENSION - 4P to 12P



PULL OUT DIRECTION →

PACKING LIST

POS.	PCS (REEL)	REEL (OUTSIDE CTN)	PCS (OUTSIDE CTN)	DIM H +0.2/-0	CTN SIZE
2P	350	7	2450	24.40	350*350*260
3P					
4P		5	1750	32.40	
5P					
6P		4	1400	44.40	
12P		3	1050	56.40	

DIM. TABLE

POS.	DIM B	DIM E ±0.10	DIM F ±0.10	DIM W +0.30/-0.10
2P	10.6		11.50	24.00
3P	13.1			
4P	15.6	28.40	14.20	32.00
5P	18.2			
6P	20.7	40.40	20.20	44.00
12P	36.0	52.40	26.20	56.00

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE MILLIMETERS. TOLERANCES: EXCEPT AS NOTED

MM	.X ± 0.35	ANGLE	± 2°
	.XX ± 0.20		
	.XXX ± 0.10		

DRAWN WY 12/16/25

CHECKED RC 12/16/25

APPROVED

CONFIDENTIAL AND PROPRIETARY
© Adam Tech. All rights reserved. This document contains confidential and proprietary information belonging to Adam Tech. It is provided solely for design and reference purposes by authorized parties. Any reproduction, distribution, display, or disclosure to third parties, in whole or in part, without the prior written consent of Adam Tech, is strictly prohibited. Adam Tech retains all rights, including copyright, trademark, trade secret, and all other intellectual property rights worldwide.

ADAM TECH

909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
adam-tech.com

TITLE 2.54mm POWER BOARD TO BOARD STACKING
CONNECTOR, FEMALE, STRAIGHT, SMT/DIP TYPE

SIZE X PART NO. ESMC12D-XX-20C2 REV. B

REF: S00242T SCALE: NTS SHEET 3 OF 3