




APPROVED: _____

DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	12/16/25	
A		UPDATE DRAWING	1/12/26	LW1/RC
B		UPDATE SPEC.	1/21/26	WY/RC



ESMC13-XX-20D1

POS.	DIM A	DIM B	DIM C	DIM D	DIM E	DIM F	DIM G
02	2.54	7.03	6.03	7.93	8.23	8.83	10.36
03	5.08	9.57	8.57	10.47	10.77	11.37	12.90
04	7.62	12.11	11.11	13.01	13.31	13.91	15.44
05	10.16	14.65	13.65	15.55	15.85	16.45	17.98
06	12.70	17.19	16.19	18.09	18.39	18.99	20.52
12	27.94	32.43	31.43	33.33	33.63	34.23	35.76

SPECIFICATIONS:

Material:

Insulator: Hi-temp thermoplastic, rated UL 94V-0

Insulator color: Black

Contact: Copper Alloy

Hold Down: Copper Alloy, Tin plated

Plating:

Gold flash over Nickel underplate on contact area,

Tin over Nickel underplate on solder tails

Electrical:

Voltage rating: 180V

Current rating: 24 Amp max (Single Contact)

Contact resistance: 10 mohms max

Insulation resistance: 10,000 Mohms min

Dielectric withstanding voltage: 1390 VAC for 1 minute

Temperature Rating:

Operating temperature: -55°C to +125°C

Environmental:

Lead free, RoHS compliant.



PACKAGED ON TAPE & REEL

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS
ARE MILLIMETERS. TOLERANCES: EXCEPT AS NOTED

MM	.X ± 0.35	ANGLE	± 2°
	.XX ± 0.20		
	.XXX ± 0.10		

DRAWN	LW1	12/16/25
CHECKED	RC	12/16/25
APPROVED		

CONFIDENTIAL AND PROPRIETARY

© Adam Tech. All rights reserved. This document contains confidential and proprietary information belonging to Adam Tech. It is provided solely for design and reference purposes by authorized parties. Any reproduction, distribution, display, or disclosure to third parties, in whole or in part, without the prior written consent of Adam Tech, is strictly prohibited. Adam Tech retains all rights, including copyright, trademark, trade secret, and all other intellectual property rights worldwide.

ADAM
TECH

909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
adam-tech.com

TITLE
2.54MM POWER BOARD TO BOARD STACKING
CONN, MALE, RIGHT ANGLE, SMT TYPE


SIZE X	PART NO. ESMC13-XX-20D1	REV. B
-----------	----------------------------	-----------

REF: S00242T	SCALE: NTS	SHEET 1 OF 3
--------------	------------	--------------


APPROVED: _____

DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
SEE SHT 1 OF 3 FOR REVISION				



Mating Application— Daughter Card to Motherboard



Mating Application— Extender Card

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS
ARE MILLIMETERS. TOLERANCES: EXCEPT AS NOTED

MM	.X ± 0.35	ANGLE	± 2°
	.XX ± 0.20		
	.XXX ± 0.10		

DRAWN LW1 12/16/25

CHECKED RC 12/16/25

APPROVED

CONFIDENTIAL AND PROPRIETARY
© Adam Tech. All rights reserved. This document contains confidential and proprietary information belonging to Adam Tech. It is provided solely for design and reference purposes by authorized parties. Any reproduction, distribution, display, or disclosure to third parties, in whole or in part, without the prior written consent of Adam Tech, is strictly prohibited. Adam Tech retains all rights, including copyright, trademark, trade secret, and all other intellectual property rights worldwide.

**ADAM
TECH**

909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
adam-tech.com

TITLE
**2.54MM POWER BOARD TO BOARD STACKING
CONN, MALE, RIGHT ANGLE, SMT TYPE**


SIZE X	PART NO. ESMC13-XX-20D1	REV. B
-----------	----------------------------	-----------

REF: S00242T	SCALE: NTS	SHEET 2 OF 3
--------------	------------	--------------


APPROVED: _____

DATE: _____ TITLE: _____



Rev	AWO #	Description	Date	Appr
SEE SHT 1 OF 3 FOR REVISION				



PULL OUT DIRECTION ➡
CARRIER DIMENSION - 2P to 3P



PULL OUT DIRECTION ➡
CARRIER DIMENSION - 4P to 12P



@ DIM. TABLE

POS.	DIM B	DIM E ±0.10	DIM F ±0.10	DIM W +0.30/-0.10
2P	10.6	28.40	11.50	24.00
3P	13.2			
4P	15.6			
5P	18.2			
6P	20.7	40.40	20.20	44.00
12P	36.0	52.40	26.20	56.00

@ PACKING LIST

POS.	PCS (REEL)	REEL (OUTSIDE CTN)	PCS (OUTSIDE CTN)	DIM H +0.2/-0	CTN SIZE
2P	600	7	4200	24.40	350*350*260
3P					
4P		5	3000	32.40	
5P					
6P					
12P		3	1800	56.40	

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS
ARE MILLIMETERS. TOLERANCES: EXCEPT AS NOTED

MM	.X ± 0.35 .XX ± 0.20 .XXX ± 0.10	ANGLE ± 2°
----	--	------------

DRAWN	LW1	12/16/25
CHECKED	RC	12/16/25
APPROVED		

CONFIDENTIAL AND PROPRIETARY
© Adam Tech. All rights reserved. This document contains confidential and proprietary information belonging to Adam Tech. It is provided solely for design and reference purposes by authorized parties. Any reproduction, distribution, display, or disclosure to third parties, in whole or in part, without the prior written consent of Adam Tech, is strictly prohibited. Adam Tech retains all rights, including copyright, trademark, trade secret, and all other intellectual property rights worldwide.

**ADAM
TECH**

909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
adam-tech.com

TITLE
2.54MM POWER BOARD TO BOARD STACKING
CONN, MALE, RIGHT ANGLE, SMT TYPE

SIZE X	PART NO. ESMC13-XX-20D1	REV. B
-----------	----------------------------	-----------

REF: S00242T	SCALE: NTS	SHEET 3 OF 3
--------------	------------	--------------