



1 GPS Antenna

- Antenna Type: Ceramic Patch
- Frequency Group: UHF (1–2 GHz)
- Applications: GPS, Beidou, Galileo, GLONASS

2 Radio Frequency Cable Assembly

- Supports IPEX, SMA, MCX, BNC
- Multiple standard cable lengths
- Customizable to application needs

3 USB Connectors

- USB4 and Type-C 3.1
- Hot-pluggable I/O interface
- EMI/RFI protection

4 Memory Connectors & Sockets

- Complete memory socket range: Compact Flash, PCMCIA, Memory Stick, Secure Digital
- Focus on ease of use, mating accuracy, and card retention
- Precision-engineered, durable contacts and PCB leads

5 Miniature Disconnecting Wire to Board

- Matched crimp housings and PCB shrouded headers
- Straight / right-angle / SMT options
- Pitch sizes: 0.8mm - 2.5mm
- Lightweight, polarized, high-reliability system

6 Flexible Printed Circuit

- Zero-wiping contact for reliability
- Single/dual row, thru-hole/SMT, vertical/horizontal
- 0.3, 0.5, 0.8, 1.00, and 1.25mm pitch

7 Flat Flex (FFC) Cables

- Centerline spacing: 0.50–2.00mm
- Flexible lengths and contact counts
- Contact layouts: same side / alternate / mixed
- Fully customizable to application needs