



## 1 USB Connectors

- USB4 and Type-C 3.1
- Hot-pluggable I/O interface
- EMI/RFI protection

## 2 D-Sub

- 9, 15, 25, 26, 37 positions
- Standard, high-density, stacked, coax, power
- Shell size, flange, mounting, termination

## 3 Modular Jacks

- 4P2C to 10P10C
- Integrated magnetics options
- Metal shielding options

## 4 HDMI Connectors

- Mini HDMI, Micro HDMI, HDMI/DisplayPort Stacked Combo, HDMI 2.1
- Mounting Flange
- Waterproof

## 5 Waterproof Audio & DC Power

- IP67 / Splash-proof protection
- Special seals, O-rings, epoxy coatings
- Engineer-tailored solutions

## 6 Radio Frequency Connectors

- RF connectors in multiple sizes: standard, miniature, micro, surface mount
- Types: BNC, TNC, SMA, SMB, N, UHF, MCX, MMCX, etc.
- Standard interfaces for high-density, lightweight applications

## 7 SATA Connectors

- Hot-plug, blind-mate SATA connectors
- Power & signal contacts combined
- Up to 3.0 Gbps performance

## 8 Wire to Board Power

- Pitch sizes: 2.50mm–6.35mm
- Secure latching system resists vibration

## 9 Disconnecting Wire to Board

- Pitch sizes: 2.54mm–3.96mm
- Secure latching system resists vibration

## 10 Heat Sinks

- Extruded and stamped types available
- Compatible with TO-220, TO-247, SOT-32 packages
- Surface finish: black anodized