



1 USB Connectors

- USB4 and Type-C 3.1
- Hot-pluggable I/O interface
- EMI/RFI protection



2 D-Sub

- 9, 15, 25, 26, 37 positions
- Standard, high-density, stacked, coax, power
- Shell size, flange, mounting, termination



3 Modular Jacks

- 4P2C to 10P10C
- Integrated magnetics options
- Metal shielding options



4 Heat Sinks

- Extruded and stamped types
- Suitable For TO-220, TO-247, and SOT-32 packaged components
- Surface finish: black anodized



5 Euro Blocks

- Pitch sizes: 3.50mm–15.00mm
- Top, side, or side-angle wire entry
- Pluggable and lever-actuated options



6 IDC Wire to Board

- Pitch sizes: 1.27, 2.54, 3.96 mm
- 18-28 AWG wires
- Long/short body, closed end or feed-through



7 Headers

- Pitch sizes: 0.8 - 5.08 mm
- Single, dual, or triple row
- Positions: 1 to 100 Solder termination
- Surface mount or through-hole mounting



8 Miniature Disconnecting Wire to Board

- Matched crimp housings and PCB shrouded headers
- Straight / right-angle / SMT options
- Pitch sizes: 0.8 - 2.5mm



9 Fiber Optic Adapters

- Align fibers for reliable optical connections
- Available in APC, FC, LC, MPO, PC, and SC types
- Configurations: simplex, duplex, 4-plex, and 8-plex



10 SFP & QSFP

- Small form factor for telecom & data applications
- 20-position SMT connector for fiber & copper
- Single- and multi-port cages
- Press-fit or through-hole mounting