



1 Headers

- Single, dual, and three-row options
- Flexible lengths and contact counts
- Straight and right-angle configurations
- Thru-hole and SMT mounting

2 Modular Jacks

- 4P2C to 10P10C
- Integrated magnetics options
- Metal shielding options

3 USB Connectors

- USB, USB4, Mini USB, Micro USB, and USB Type C 3.1
- Hot-pluggable I/O interface
- EMI/RFI protection

4 Miniature Disconnecting Wire to Board

- Matched crimp housings and PCB shrouded headers
- Straight / right-angle / SMT options
- Pitch sizes: 0.8 - 2.5mm

5 Flexible Printed Circuit

- Zero-wiping contact for reliability
- Single/dual row, thru-hole/SMT, vertical/horizontal
- 0.3, 0.5, 0.8, 1.00, 1.25 pitch (mm)

6 Flat Flex (FFC) Cables

- Centerline spacing: 0.50–2.00mm
- Flexible lengths and contact counts
- Contact layouts: same side / alternate / mixed

7 HDMI Connectors

- Mini HDMI, Micro HDMI, HDMI/DisplayPort Stacked Combo, HDMI 2.1
- Mounting Flange
- Waterproof

8 Wire to Board Power

- Pitch sizes: 2.50mm–6.35mm
- Secure latching system resists vibration

9 Disconnecting Wire to Board

- Pitch sizes: 2.54mm–3.96mm
- Secure latching system resists vibration
- Wire housings, headers, and crimp terminals

10 High Speed Board to Board

- Speeds up to 28 Gbps
- Pitch options: 0.5mm or 0.8mm
- Stack height: 5mm